



**Patented system**  
**Innovative drive solution:**  
**one motor – two contra**  
**rotating mixing tools**



**Timer for TwinMix 1800 T**  
**for setting the requested**  
**mixing time (accessory)**

**50 kg**

| SPECIFICATIONS            | TWINMIX 1800/1800 T   |
|---------------------------|---|
| Power input               | 1800 W  |
| Rated voltage             | 230 V ~   |
| Rated speed mixing rod    | 250/450 rpm   |
| Rated speed mixing paddle | 20/36 rpm   |
| Bucket size               | 65 l  |
| Spindle connection        | M 14/Special  |
| Weight                    | 70.0 kg   |
| Order no.                 | 07621000/07623000   |
| Supplied                  | on a pallet incl. mixing rod, mixing paddle, bucket 65 l and transport carriage |

## Mixing stations TwinMix 1800/TwinMix 1800 T

### The mobile stations for thorough mixing with a wide range of application

#### USE:

- Homogenous and lump free mixing of numerous materials with different viscosity
- Especially convenient for the mixing of self-levelling floor levelling compounds, plaster, thin-bed mortar, fillers
- Building construction and civil engineering, landscaping, floor renovators, tilers

#### FEATURES:

- Mixing paddle with scraper – avoids material deposits on the bucket rim and ensures together with a fast running inner rod a better mixing
- Two electronic speed levels – start mixing function with reduced speed
- Transport carriage with handles and big wheels – mobile use of the station at the construction sites, also at rough terrain
- Robust universal motor – very high pulling power
- Electronic – soft start, constant speed, temperature control and overload cut-off
- Switch with dust protection and protection against re-start
- Safety Switch – cut-off in case of opening the hood, protection of the operator
- Connection for dust exhaust Ø 35 mm as well as funnel tube with brushes – dust reduced filling and mixing of the materials
- Tipper (accessory) especially designed for clean and precise pouring of self-levelling filler and levelling compounds
- Mixing carriage (supplied) can be used separate from the station – flexible and mobile at the job site

#### ACCESSORIES



Transport carriage with 2 big wheels  
 Order no.: 09Z11000



Tipper with 4 wheels (2 steerable)  
 Order no.: 09Z12000

Timer for TwinMix 1800 T  
 Order no.: 32352000

Bucket 65 l  
 Order no.: 32341000



TwinMix 1800 T expected to be available from 3rd quarter 2017

## Fast, uninterrupted work when using several mixing carriages, f. e. for levelling filler

- ☞ saves time and costs
- ☞ reduces the risk that the material is setting too fast in wet-on-wet cycle

saves at least **50% time**

10:15



Mixture 1



Mixture 2

10:20



Mixture 2



Mixture 3

### VERSATILE APPLICATION POSSIBILITIES



masonry mortar



thin-bed mortar



plaster



floating screed



tile cement



two-component materials



insulation board adhesive



screed



filler

### Health protecting mixing (dust reduced construction site, especially in the interior)

- ☞ Hazardous dust (e. g. silica dust) has to be suctioned by a Dust Class M Vacuum Cleaner! For our electric power tools we are recommending to use a Vacuum Cleaner of our Eibenstock DSS range!

