





## The powerful stirrer up to 80 kg of mixing material



## **FEATURES:**

- Clockwise/anticlockwise: two mixed effects simply by switching – no need to change of the stirring rods
- Two contra rotating stirring rods no counter torque, easy handling, saves time and effort
- Electronic switch dust protected
- Soft start for less splashing
- Temperature control
- Stepless speed regulation and constant speed optimum settings on the material to be mixed
- Wide, trapezium design, ergonomic handles and a high positioned center of gravity – easy, well balanced guiding of the machine for greater leverage
- Cap with labyrinth-guide protection against dirt, stones, splash water etc.
- Damping and protection elements made of polyurethane
   protection of the machine and the surface in case of unintentional fall
- PUR-construction site cable and a protected cable outlet for heavy duty use

Technische Daten	EZR 24 R R/L SET	
Power input	1800 W	
Rated voltage	230 V ~	
Rated speed	180-440 rpm	
Total diameter rods	230 mm	
Spindle connection	Special	
Weight	7.1 kg	
Bestellnummer	0774W000	
Supplied	in a box incl. stirring rods Z 230	

g	Stirring rods	Order no.
	Z 200 (1 pair), up to 40 kg	31620000
	Z 220 (1 pair), up to 60 kg	31610000
	Z 230 (1 pair), up to 80 kg	31630000

## USE:

- Mixing clockwise of highly viscous and stiff materials,
   e.g. tile cement, ready-mixed mortar and plaster, screed,
   epoxy resins, sealants, granules, multi-component
   materials, coatings
- Mixing anticlockwise of building materials with low and middle viscosity, e.g. paint, glue, filler and leveling compounds
- Drywall construction, tiler, painter and plasterer, civil engineering, gardening and landscaping, floor renovators

Elektrowerkzeuge GmbH Eibenstock Auersbergstraße 10 D-08309 Eibenstock

Phone: +49 37752 503-0
Fax: +49 37752 2019
Web: www.eibenstock.com
E-Mail: office@eibenstock.com

Certified according to DIN EN ISO 9001:2015 Technical changes excepted! Illustrations may vary! Your dealer:

19290ENG - Stand 03/21