









The lightweight stirrer up to 30 kg

USE:

- Mixing of building materials with low viscosity, e.g. paint, glue, filler and leveling compounds, tile cement
- Drywall construction, tiler, painter and plasterer

FEATURES:

- Electronic switch stepless speed control for less
- M 14 female direct stirrer connection effective power transmission, high concentricity
- Large handles effortless working
- T-wise handling comfortable mixing

The handy stirrer up to 40 kg

USE:

- Mixing of building materials with low and middle viscosity, e.g. paint, glue, filler and leveling compounds, tile cement, ready-mixed mortar

 – Drywall construction, tiler, painter and plasterer

FEATURES:

- Electronic switch stepless speed control for less
- M 14 female direct stirrer connection effective power transmission, high concentricity
- Space-saving metal bow handle handy, easy to put down, comfortable transport
- Soft grip handle less vibration, non-slip

SPECIFICATIONS	EHR 14.1 SK SET
Power input	960 W
Rated voltage	230 V ~
Rated speed	0-390 rpm
No-load speed	590 rpm
Max. basket diameter	120 mm
Spindle connection	M 14 female
Weight	2.9 kg
Order no.	07753000
Supplied	in a box incl. stirring rod WG 120

SPECIFICATIONS	EHR 15.1 SB SET
Power input	1.050 W
Rated voltage	230 V ~
Rated speed	0-450 rpm
No-load speed	800 rpm
Max. basket diameter	120 mm
Spindle connection	M 14 female
Weight	3.1 kg
Order no.	07760000
Supplied	in a box incl. stirring rod WG 120



